



TO LOCK IN A 4±0.08mm Ø HOLE
1.6mm PANEL THICKNESS. (BOTH SIDES)

ITEM NO.	L	
	mm. ± 0.4	Inches ±.015
01-27-30	3.0	.118
01-27-40	4.0	.157
01-27-50	5.0	.196
01-27-60	6.0	.236
01-27-80	8.0	.315
01-27-100	10.0	.394
01-27-120	12.0	.472
01-27-140	14.0	.551
01-27-160	16.0	.630
01-27-180	18.0	.709

PACKAGING : 1000 PER BAG

NYLON 66 RATED UL94V-0 AVAILABLE ON REQUEST.
TO ORDER ADD SUFFIX "X" TO PART NUMBER

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E41938
COLOR	NATURAL
ASTM	D 4066, PA111
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	12

					BY	DATE	Title PCB SUPPORT, DUAL LOCK, METRIC	Issue
							File No. 0127series	A
							ALL ELECTRONICS HARDWARE, INC. 2642 CORPORATE PARKWAY ALGONQUIN, IL. 60102 1-800-778-7234	
A	.Added mounting parameters	3-1-12	FL	REVIEWED	F. LODI	03-01-12		03-01-12
No	Revision	Date	Init	DRAWN	F. LODI	11-21-09.		