



PANEL THICKNESS RANGE: .030 To .062 (0.8 to 1.6)

ITEM NO	W1		W2		L1		L2		H1	
	Reference Inches	mm	Reference Inches	mm	Inches	mm	Reference Inches	mm	Inches	mm
03-69-14	.78	19.8	.46	11.8	.64	16.3	.29	7.4	.16	4.1
03-69-19	1.06	26.8	.66	16.8	.98	24.9	.59	15	.15	3.9
03-69-21	1.13	28.8	.66	16.8	.98	24.9	.59	15	.15	3.9
03-69-27	1.37	34.8	.90	22.9	1.31	33.3	.91	23.1	.17	4.3

RECOMMENDED CUT-OUT DIMENSIONS

ITEM NO	W3		L4		H2		R1		R2	
	+012 (0.3) / -0.0 Inches	mm	+012 (0.3) / -0.0 Inches	mm	+008(0.2) / -0.00 Inches	mm	Inches	mm	Inches	mm
03-69-14	.551	14	.484	12.3	.106	2.7	.079	2	.039	1
03-69-19	.756	19.2	.831	21.1	.098	2.5	.079	2	.039	1
03-69-21	.827	21	.827	21	.094	2.4	.04	1	.062	1.6
03-69-27	1.06	27	1.14	29	.118	3	NA		NA	

PACKAGING : 1000 PER BAG

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E41938
COLOR	NATURAL
ASTM	D 4066, PA111
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	12

UL 94V-O MATERIAL AVAILABLE UPON REQUEST  
TO ORDER ADD SUFFIX "X" TO ITEM NUMBER

					By	Date	Title WIRE ROUTING EDGE PROTECTOR	Issue O
				CUSTOMER				
				VERIFIED			File No.	03-69 series
		12-12-12	FL	REVIEWED			ALL ELECTRONICS HARDWARE, INC. 2642 CORPORATE PARKWAY ALGONQUIN, IL. 60102 1-800-778-7234	
No	Revision	Date	By	DRAWN	F. L	09-23-14		09-23-14