



| ITEM NUMBER | A Holding Diameter Range | | L (Reference) | |
|-------------|-----------------------------|-------------|------------------|------|
| | Inches | mm | Inches | mm |
| 03-70-350 | .30 - .40 | 7.6 - 10.2 | 1.07 | 27.2 |
| 03-70-450 | .40 - .50 | 10.2 - 12.7 | 1.23 | 31.2 |
| 03-70-750 | .70 - .80 | 17.8 - 20.3 | 1.58 | 40.1 |

| | |
|---------------------|----------------------------|
| ADHESIVE | RUBBER |
| CARRIER | POLYETHYLENE FOAM |
| THICKNESS | .040 (1mm) |
| COLOR | WHITE |
| UL FILE NO. | NA |
| RoHS COMPLIANCE | YES |
| SERVICE TEMPERATURE | 14 to 113°F (-10 to 45 °C) |
| MR NUMBER | 59 |

| | |
|----------------------------|----------------------------|
| MATERIAL | NYLON 66 |
| UL RATING | 94V-2 |
| UL FILE NO. | E41938 |
| COLOR | NATURAL |
| RoHS COMPLIANCE | YES |
| SERVICE TEMPERATURE (REF.) | -40 to 185jF (-40 to 85jC) |
| MR NUMBER | 12 |

Note: Acrylic adhesive available on request.

UL 94V-O material available on request.
To order add suffix "X" to Item number.

| | | | | | | | | |
|----|----------------------------------|---------|-------|--|----|--------|--|--|
| | | | | CUSTOMER'S APPROVAL | | | Title TWIST CLIP ON BASE 03-70 SERIES. | |
| | | | | VERIFIED BY | | | Part No. SEE TABLE | |
| | | | | REVIEWED BY | | | Issue A | |
| | | | | DRAWN BY | FL | 9-8-14 | 9-18-20 | |
| | | | | DIMENSIONS Inches (mm) Tolerance (unless noted) .xx = ±.010 . xxx = .005 | | | Drwg. type CATALOG | |
| A | Changed adhesive specs. to MR-59 | 9-18-20 | FL | ALL ELECTRONICS HARDWARE INC. 2642 CORPORATE PARKWAY Algonquin, IL. 60102 1-800-778-7234 | | | File No. 03-70Series | |
| No | Revisions | Date | Init. | | | | | |