



To install: Insert in hole, press top to lock.

To remove : pull top.

Color: Tan

Ideal for use in short time high temperature resistance applications, such as heat spikes encountered in wave soldering.

Packaging : 1000 Pcs / Bag

MATERIAL	NYLON 4/6
UL RATING	94V-2
UL FILE NO.	E70062
COLOR	TAN
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 306°F (-40 to 152°C)
MR NUMBER	33

ITEM NO.	HOLE DIA.		PANEL THICKNESS		L1 Inches (mm)	L2 Inches (mm) ± .012. (0.3)	W1 Inches (mm)	W2 Inches (mm)
	In	mm	Inches	mm				
06-01-3035HR			.039 - .079	1 - 2		.14 (3.5)		
06-01-3045HR			.079 - .118	2 - 3		.18 (4.5)		
06-01-3055HR	.122 - .126		.118 - .157	3 - 4	.063	.22 (5.6)	.118	.252
06-01-3065HR	3.1 - 3.2		.157 - .197	4 - 5	(1.6)	.26 (6.5)	(3)	(6.4)
06-01-3080HR			.197 - .236	5 - 6		.31 (8)		
06-01-3535HR	.142 - .146		.047 - .083	1.2 - 2.1	.063	.14 (3.5)	.138	.252
06-01-3545HR	3.6 - 3.7		.083 - .122	2.1 - 3.1	(1.6)	.18 (4.5)	(3.5)	(6.4)
06-01-3555HR			.118 - .157	3 - 4		.22 (5.6)		
06-01-4050HR			.098 - .138	2.6 - 3.5		.20 (5)		
06-01-4060HR			.138 - .177	3.5 - 4.5		.24 (6)		
06-01-4070HR	.161 - .165		.177 - .217	4.5 - 5.5	.071	.28 (7.2)	.157	.315
06-01-4080HR	4.1 - 4.2		.217 - .256	5.5 - 6.5	(1.8)	.32 (8)	(4)	(8)
06-01-4100HR			.295 - .335	7.5 - 8.5		.39 (10)		

				ALL ELECTRONICS HARDWARE , INC. 2642 CORPORATE PARKWAY ALGONQUIN, IL. 60102 1-800-778-7234		Title SNAP RIVETS, HI TEMP.		Issue A	
A	Corrected P/N table.	8/5/09	FL			File No. 0601HR RIVETS		Date 08/05/09	
No	Revision	Date	Init						