



# 06-01 rivets



For UL94V-0 Nylon : add suffix "X" to Item No.  
 Standard Color :Black.  
 For color white add suffix W to item number.  
 Other colors available on request.  
 Packaging : 1000 Pcs / Bag.

MATERIAL	NYLON 6
UL RATING	94V-2
UL FILE NO.	E41871
COLOR	Natural.
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to185°F (-40 to85°)
MR NUMBER	31

MATERIAL	NYLON 6/66
UL RATING	94V-0
UL FILE NO.	E41871
COLOR	BLACK
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 - 185°F (-40 - 85°C)
MR NUMBER	32.

ITEM NO.	D Panel Hole Ø Inches mm	T Panel Thickness Inches mm	L1 Inches (mm).	L2 Inches (mm)	W1 Inches (mm)	W2 Inches (mm)	Holding Force (Minimum) Lb. (Kg)				
06-01-2024	.083 - .087 2.1 - 2.2	.024 -.047	.047 (1.2)	.09 (2.4)	.79 (2)	.165 (4.2)	6.6 (3)				
06-01-2032		.051 -.079		.13 (3.2)							
06-01-2040		.083 -.110		.16 (4)							
06-01-2048		.114 -.142		.19 (4.8)							
06-01-2056		.146 -.173		.22 (5.6)							
06-01-2064	.173 -.197	.25 (6.4)									
06-01-2632	.106 - .110 2.6 - 2.7	.039 -.079	.055 (1.4)	.13 (3.2)	.102 (2.6)	.197 (5)	6.6 (3)				
06-01-2642		.079 -.118		.17 (4.2)							
06-01-2648		.106 -.142		.19 (4.8)							
06-01-2655		.134 -.169		.22 (5.6)							
06-01-2664		.169 -.205		.25 (6.4)							
06-01-2672	.201 -.236	.28 (7.2)									
06-01-3035	.122 - .126 3.1 - 3.2	.039 -.079	.063 (1.6)	.14 (3.5)	.118 (3)	.252 (6.4)	15.4 (7)				
06-01-3045		.079 -.118		.18 (4.5)							
06-01-3055		.118 -.157		.22 (5.6)							
06-01-3065		.157 -.197		.26 (6.5)							
06-01-3075		.197 -.236		.30 (7.5)							
06-01-3080		.217 -.256		.32 (8)							
06-01-3090		.256 -.295		.35 (9)							
06-01-3100		.295 -.335		.39 (10)							
06-01-3230		.807 -.846		.906 (23)							
06-01-3535		.142 - .146 3.6 - 3.7		.047 -.083				.063 (1.6)	.14 (3.5)	.138 (3.5)	.252 (6.4)
06-01-3545	.083 -.118		.18 (4.5)								
06-01-3550	.106 -.142		.20 (5)								
06-01-3555	.118 -.157		.22 (5.6)								
06-01-3560	.146 -1.81		.24 (6)								
06-01-3570	.177 -.217		.28 (7.2)								
06-01-3580	.217 -.256		.32 (8)								
06-01-4050	.161 - .165 4.1 - 4.2	.098 -.138	.071 (1.8)	.20 (5)	.157 (4)	.315 (8)	44.0 (20)				
06-01-4060		.138 -.177		.24 (6)							
06-01-4070		.177 -.217		.28 (7.2)							
06-01-4080		.217 -.256		.32 (8)							
06-01-4090		.256 -.295		.35 (9)							
06-01-4100		.295 -.335		.39 (10)							
06-01-4120		.354 -.413		.47 (12)							
06-01-5045	.201 - .205 5.1 - 5.2	.059 -.098	.087 (2.2)	.18 (4.5)	.197 (5)	.354 (9)	55 (25)				
06-01-5055		.098 -.138		.22 (5.6)							
06-01-5065		.138 -.177		.26 (6.5)							
06-01-5075		.177 -.217		.30 (7.5)							
06-01-5085		.217 -.256		.34 (8.5)							
06-01-5095		.256 -.295		.37 (9.5)							
06-01-5105		.295 -.335		.41 (10.5)							
06-01-6060	.240 - .244 6.1 - 6.2	.098 -.157	.098 (2.5) .118 (3)	.24 (6)	.2 (6)	.4 (12)	66 (30)				
06-01-6080		.138 -.217		.32 (8)							
06-01-6026		.846 -.925		1.024 (26.0)							
06-01-6028		.925 -1.00		1.122 (28.5)							

F	Added P/N 06-01-3230, corrected extraxion force	07-26-19	FL		By	Date	Title	SNAP RIVETS	Issue
E	Added P/N 06-01-6026 & 06-01-2028	03-30-17	FL	CUSTOMER			File No.	06-01rivets	
D	Added MR32 (V-0) material	11-14-16	FL	VERIFIED			ALL ELECTRONICS HARDWARE, INC. 2642 CORPORATE PARKWAY ALGONQUIN, IL. 60102 1-800-778-7234		F 07/26/19
C	Corrected some table's errors	11-17-14	FL	REVIEWED					
No	Revision	Date	By	DRAWN	F. L	03-03-09			