



ITEM No	HOLE DIA		HOLDING THICKNESS		L (REF)		W		H	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
06-04-100	.187	4.7	.062 - .187	1.6 - 4.8	.295	7.5	.435	11.0	.075	1.9
06-04-110	.217	5.5	.095 - .158	2.4 - 4	.440	11.18	.370	9.4	.079	2.0
06-04-200	.189	4.8	.158 - .281	4.0 - 7.1	.382	9.7	.429	10.9	.059	1.5
06-04-300	.187	4.7	.312 - .440	2.9 - 11.2	.535	13.6	.281	7.1	.075	1.9
06-04-400	.252	6.4	.280 - .500	7.1 - 12.7	.622	15.8	.469	11.9	.079	2.0
06-04-500	.189	4.8	.039 - .375	1.0 - 9.5	.421	10.7	.281	7.1	.063	1.6
06-04-600	.125	3.18	.031 - .140	0.8 - 3.56	.190	4.82	.187	4.75	.047	1.2
06-04-900	.252	6.4	.059 - .252	1.6 - 6.4	.366	9.3	.437	11.1	.185	4.7

PACKAGING: 1000 PCS. PER BAG
 COLOR: NATURAL. BLACK AVAILABLE ON REQUEST

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E41938
COLOR	NATURAL
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	12

No	Revision	Date	Init	DRAWN	FL	Date	BY	Title	Issue
								RIVETS, NYLON	
				CUSTOMER'S OK				File No. 06-04rivets	
B	added part number 06-04-600	6-18-19	FL	VERIFIED				ALL ELECTRONICS HARDWARE, INC. 2642 CORPORATE PARKWAY ALGONQUIN, IL. 60102 1-800-778-7234	B 06-18-19
A	added REF to "L", corrected 06-04-110 and 06-04-200.	2-21-12	FL	REVIEWED	DP	06-18-19			
No				DRAWN	FL	06-28-11			