


ITEM NO.	L	
	Inches ±.015	mm ±0.08
07-14-2-40	.250	6.4
07-14-2-50	.312	7.9
07-14-2-60	.375	9.5
07-14-2-70	.437	11.1
07-14-2-80	.500	12.7
07-14-2-100	.625	15.9
07-14-2-120	.750	19.1
07-14-2-140	.875	22.2
07-14-2-160	1.000	25.4

MOUNTING HOLE DIA. = .232 ±.003 (5.9 ±0.08)
 MATERIAL THICKNESS = .087 (2.2)
 FOR USE WITH # 8 (M4) SCREW

PACKAGING : 1000 PER BAG



TYPICAL APPLICATION

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E41938
COLOR	NATURAL
ASTM	D 4066, PA111
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	12

UL 94V-0 MATERIAL AVAILABLE UPON REQUEST
 TO ORDER ADD SUFFIX "X" TO ITEM NUMBER

					BY	DATE	Title SPACER, SCREW INSULATOR	
							Part No.	Issue
							See table	0
					FL	3-27-17	DIMS. Inches (mm) Tolerance (unless noted) .xx = ±.010 .xxx = .005	
					ALL ELECTRONICS HARDWARE INC. 2642 CORPORATE PARKWAY ALGONQUIN, ILLINOIS . 60102 1-800-778-7234		Drwg. type Catalog	03/27/17
No	Revision	Date	Init.				File No. 07-14-2 series	