

03 SERIES






FIGURE 1

FIGURE 2



- Chemical and heat resistant
- Two mounting methods; via oval center hole (see figure 1) or via outside slits (see figure 2)
- Spaces and insulates
- Material: UL94V-0 (E58608)



ITEM NO.	L		Mounting Method	Mounting Method
	inches	(mm)		
09-03-20	.079	(2.0)	See Figure 1	See Figure 2
09-03-30	.118	(3.0)		
09-03-40	.158	(4.0)		
09-03-50	.197	(5.0)		
09-03-60	.236	(6.0)		
09-03-70	.276	(7.0)		
09-03-80	.315	(8.0)		
09-03-90	.354	(9.0)		
09-03-100	.394	(10.0)		
09-03-120	.472	(12.0)		
09-03-150	.591	(15.0)		
Tolerance ±	.004	(.1)		

ITEM NO. 09-03-Series	
COLOR:	Black
PACKAGING:	1000/bag
MATERIAL:	Olefin Elastomers

02 SERIES






FIGURE 1

FIGURE 2



- Chemical and heat resistant
- Two mounting methods; via oval center hole (see figure 1) or via outside slits (see figure 2)
- Spaces and insulates
- Material: UL94V-0 (E58608)



ITEM NO.	L		Mounting Method	Mounting Method
	inches	(mm)		
09-02-20	.079	(2.0)	See Figure 1	See Figure 2
09-02-30	.118	(3.0)		
09-02-40	.158	(4.0)		
09-02-50	.197	(5.0)		
09-02-60	.236	(6.0)		
09-02-70	.276	(7.0)		
09-02-80	.315	(8.0)		
09-02-90	.354	(9.0)		
09-02-100	.394	(10.0)		
09-02-120	.472	(12.0)		
09-02-150	.591	(15.0)		
Tolerance ±	.004	(.1)		

ITEM NO. 09-02-Series	
COLOR:	Black
PACKAGING:	1000/bag
MATERIAL:	Olefin Elastomers