



PACKAGING :500 PER BAG
 V-O RATED NYLON 66 AVAILABLE UPON REQUEST
 TO ORDER ADD SUFFIX "X" TO PART NUMBER.

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E70062
COLOR	NATURAL
ASTM	D 4066, PA111
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	01

ITEM NO	L1		L2		L3	
	Inches	mm	Inches	mm	Inches	mm
UL94-V2	Reference		±.025	± 0.64	±.016	±0.41.
14-02-250	2.5	63.5	1.5	38.1		
14-02-300	3.0	76.2	2.0	50.8		
14-02-350	3.5	88.9	2.5	63.5		
14-02-400	4.0	101.6	3.0	76.2		
14-02-450	4.5	114.3	3.0	76.2		
14-02-451	4.5	114.3	3.5	88.9		
14-02-500	5.0	127	4.0	101.6		
14-02-550	5.5	139.7	4.5	114.3		
14-02-600	6.0	152.4	5.0	127		
14-02-650	6.5	165.1	5.0	127		
14-02-651	6.5	165.1.	5.5	139.7		
14-02-700	7.0	177.8	6.0	152.4		
14-02-750	7.5	190.5	6.5	165.1		
14-02-800	8.0	203.2	7.0	177.8		
14-02-800-3	8.0	203.2	7.0	177.8	3.5	88

				Name	Date	Title CARD GUIDE- 14-02 SERIES			
I	L2 for 14-02-650 was 5.02	11/09/11	FL	Drawn By	FL		07-07-03		
H	Added material's box	05/30/08	FL	Checked By					
G	Tolerance of cntr hole	10/22/04	FL	TOLERANCE UNLESS NOTED	.XX = .010 .XXX = .005				
F	added P/N -651	09/23/04	gfl	ALL ELECTRONICS HARDWARE 2642 Corporate Pkwy. Algonquin IL, 60102. Tel. 1-800-778-7234		Drawing Type	CATALOG	Issue	I
E	Corrected slot tol.	08/23/04	gfl			File Number	1402CAT	11/09/11	
A	Added -451	07/08/03	gfl						
No	Change	Date	Init						