



ITEM NO	L1		L2		L3	
	±.030 IN.	± 0.76 mm	± .024 IN.	± 0.61 mm	±.016 IN.	± 0.41 mm
14-07-2250	2.5	(63.5)	2.0	(50.8)		
14-07-2300	3.0	(76.2)	2.5	(63.5)		
14-07-2350	3.5	(88.9)	3.0	(76.2)		
14-07-2400	4.0	(101.6)	3.5	(88.9)		
14-07-2450	4.5	(114.3)	4.0	(101.6)		
14-07-2500	5.0	(127)	4.5	(114.3)		
14-07-2550	5.5	(139.7)	5.0	(127)		
14-07-2600	6.0	(152.4)	5.5	(139.7)		
14-07-2650	6.5	(165.1)	6.0	(152.4)		
14-07-2700	7.0	(177.8)	6.5	(165.1)		
14-07-2750	7.5	(190.5)	7.0	(177.8)		
14-07-2800	8.0	(203.2)	7.5	(190.5)		
14-07-2850	8.5	(215.9)	8.0	(203.2)		
14-07-3700	7.0	(177.8)	6.5	(165.1)	3.25	(82.5)
14-07-3750	7.5	(190.5)	7.0	(177.8)	3.5	(88.9)
14-07-3800	8.0	(203.2)	7.5	(190.5)	3.75	(95.3)
14-07-3850	8.5	(215.9)	8.0	(203.2)	4.0	(101.6)

V-0 RATED NYLON AVAILABLE UPON REQUEST.
TO ORDER ADD SUFFIX "X" TO PART NUMBER.
PACKAGING = 500 PER BAG .

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E70062
COLOR	NATURAL
ASTM	D 4066, PA0113
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	01

				Name	Date	Title	CARD GUIDES, 14-07 SERIES		
				Drawn By	FL	07-02-03			
				Checked By					
G	Re-drawn on Mac	05/05/09	FL	Tolerance, unless noted	.XX = .010	.XXX = .005			
F	General update, new address	06/25/08	FL	ALL ELECTRONICS HARDWARE, INC. 2642 CORPORATE PARKWAY ALGONQUIN, ILLINOIS, 60102 TEL. 1 800 778 7234			Drawing Number	1407F	Issue G
E	added mtl. box and slot callout	07/03/05	FL				file Number		
D	REMOVED SLOT NOTE	08/23/04	FL						
No	Change	Date	Init						