


# 19-SC & -HTC WIRE NUTS



ITEM NO.	COLOR	VOLTS	TEMP.	WIRE RANGE		PIECES PER BAG
				MIN.	MAX	
19-SC-GY-M	GRAY	300	105°C	No 22 thru No 14 AWG		1000
				2 #22	1 #14 + 1 #20	
19-SC-BL- M	BLUE	300	105°C	No 22 thru No 14 AWG		1000
				2 #22	3 #16	
19-SC-OR-D	ORANGE	600*	105°C	No 22 thru No 14 AWG		500
				1 #18 + 1 #20	4 #16 + 1 #20	
19-SC-YW-D	YELLOW	600*	105°C	No 22 thru No 10 AWG		500
				3 #20	1 #10 + 2 #14 + 1 #16	
19-SC-RD-D	RED	600*	105°C	No 18 thru No 10 AWG		500
				3 #18	3 #10	
19-HTC-BK-M	BLACK	300	150°C	No 22 thru No 14 AWG		1000
				3 #22	2 #16	
19-HTC-BK-D	BLACK	300	150°C	No 22 thru 14 AWG		500
				3 #20	2 #14 + 1 #16	

\* 1,000 VOLTS MAX IN FIXTURES AND SIGNS

ITEM NO.	A DIA.		B DIA.		C DIA.		D		E	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
19-SC-GY-M	.150	3.8	.264	6.7	.339	8.6	.228	6.2	.598	15.2
19-SC-BL- M	.161	4.1	.276	7	.386	9.8	.232	7.2	.693	17.6
19-SC-OR-D	.197	5	.390	9.9	.480	12.2	.307	9.6	.866	22.
19-SC-YW-D	.236	6	.441	11.2	.551	14	.311	12	.945	24
19-SC-RD-D	.295	7.5	.511	13	.645	16.4	.360	9.1	1.042	26.5
19-HTC-BK-M	.150	3.8	.264	6.7	.339	8.6	.228	5.8	.598	15.2
19-HTC-BK-D	.197	5	.390	9.9	.480	12.2	.307	7.8	.866	22

MATERIAL: HIGH DIELECTRIC PLASTIC, RATED UL94-V2.  
UL LISTED, & CSA APPROVED.

					BY	DATE	Title	
							<b>WIRE CONNECTORS SC &amp; HTC SERIES</b>	
					VERIFIED		Part No.	Issue
					REVIEWED	FL	.07-08-09	SEE TABLE
					DRAWN	FL	.07-08-09	0
					DIMENSIONS Inches (mm) Tolerance .xxx = ± .062			0
					ALL ELECTRONICS HARDWARE INC. 2642 Corporate Parkway Algonquin, IL. 60102 1-800-778-7234			07/08/09
No	Revision	Date	Init.		Drwg. type	CATALOG	File No.	19SCHTC series