





08-04 GROMMETS



SECT. A-A



APPLICATION

ITEM NO	A DIA. ± .020 (0.51)		C DIA. Reference.		D ± .015 (0.38)	
	Inches	(mm)	Inches	(mm)	Inches	(mm)
08-04-250	.562	(14.3)	1/4	(6.35)	.28	(7.1)
08-04-375	.672	(17.1)	3/8	(9.5)	.28	(7.1)
08-04-500	.86	(21.8)	1/2	(12.7)	.25	(6.4)
08-04-750	1.234	(31.34)	3/4	(19.05)	.31	(7.9)

B PANEL HOLE DIA.		E PANEL THICKNESS.	
Inches	(mm)	Inches	(mm)
.37	(9.35)	3/32	(2.36)
.49	(12.4)	1/16	(1.57)
.69	(17.5)	1/16	(1.57)
1.0	(25.4)	1/16	(1.57)

MATERIAL	PVC. SOFT
UL RATING	NR
COLOR	BLACK
DUROMETER	60, SHORE A
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	32 to 132°F (0 to 50°C)
MR NUMBER	21

PACKAGING: 1000 PER BAG

				Drwn. by:	Name	Date	Title		
					gfl	11/04/04	HOLE GROMMETS, INSULATING		
F	Added application, split table	12/28/12	LF	Unit:	INCHES	(mm)			
E	revised table	02/12/09	fl	Tolerance unless noted			Part No.	Issue	
D	Corrected dim A for P/N -750	02/11/09	fl	FRACTIONS: ± 1/64			08-04-SERIES	F	
C	Re-drawn in Graphite V8	10/20/08	fl	ALL ELECTRONICS HARDWARE, INC. 2642 CORPORATE PARKWAY ALGONQUIN, ILLINOIS 60102 1-800-778-7234			Drwng. Type	12-28-12	
B	Changed material specs.	04/06/06	fl				File No.		GROMMETS0804F
No	Revision	Date	Init						