


MATERIAL NYLON 66  
 UL RATING 94V-2  
 UL FILE NO. E70062  
 COLOR NATURAL  
 ASTM D 4066, PA111  
 RoHS COMPLIANCE YES  
 TEMPERATURE RANGE (REF.) -40 to 185°F (-40 to 85°C)  
 MATERIAL NUMBER MR-01



Route and secure wires or bundles with a simple twist.  
 Arrow head snap locks easily into boards.  
 Lifts wires off board, away from panels, moving parts or hot components.  
 Parts with dimension L1 from 1" to 2", in increments of 1/8" (3.2), are available upon request. Consult factory.  
**Standard packaging = 1000 pcs per bag.**  
**For parts with L1 longer than 1" packaging =500pcs/bag.**  
 All dimensions are for reference only.

NYLON RATED UL94V-0 AVAILABLE ON REQUEST  
 TO ORDER ADD SUFFIX "X" TO ITEM NUMBER

CLAMP BASE						DIMENSION L1
	BUNDLE Ø RANGE .20 to .30 (5.1to 7.6)	BUNDLE Ø RANGE .30 to .40 (7.6to 10.2)	BUNDLE Ø RANGE .40 to .48 (10.2to 12.2)	BUNDLE Ø RANGE .50 to .60 (12.7to 15.2)	BUNDLE Ø RANGE .70 to .80 (17.8 to 20)	
 HOLE Ø= .156±.003 (4±0.08) PANEL THICKNESS RANGE = .015 to .090 (0.38 to 2.28)	03-43-1-30 03-43-1-40 03-43-1-50 03-43-1-60 03-43-1-70 03-43-1-80 03-43-1-90 03-43-1-100 03-43-1-120 03-43-1-140 03-43-1-160	03-39-1-30 03-39-1-40 03-39-1-50 03-39-1-60 03-39-1-70 03-39-1-80 03-39-1-90 03-39-1-100 03-39-1-120 03-39-1-140 03-39-1-160	03-35-1-30 03-35-1-40 03-35-1-50 03-35-1-60 03-35-1-70 03-35-1-80 03-35-1-90 03-35-1-100 03-35-1-120 03-35-1-140 03-35-1-160	03-36-1-30 03-36-1-40 03-36-1-50 03-36-1-60 03-36-1-70 03-36-1-80 03-36-1-90 03-36-1-100 03-36-1-120 03-36-1-140 03-36-1-160	03-44-1-30 03-44-1-40 03-44-1-50 03-44-1-60 03-44-1-70 03-44-1-80 03-44-1-90 03-44-1-100 03-44-1-120 03-44-1-140 03-44-1-160	.125 (3.2) .187 (4.8) 250 (6.35) 312 (7.9) 375 (9.5) 437 (11.1) 500 (12.7) 562 (14.3) 625 (15.9) 750 (19.1) 875 (22.2) 1.00 (25.4)
 HOLE Ø= .187±.003 (4.75±0.08) PANEL THICKNESS RANGE = .015 to .090 (0.38 to 2.28)	03-43-30 03-43-40 03-43-50 03-43-60 03-43-70 03-43-80 03-43-90 03-43-100 03-43-120 03-43-140 03-43-160	03-39-30 03-39-40 03-39-50 03-39-60 03-39-70 03-39-80 03-39-90 03-39-100 03-39-120 03-39-140 03-39-160	03-35-30 03-35-40 03-35-50 03-35-60 03-35-70 03-35-80 03-35-90 03-35-100 03-35-120 03-35-140 03-35-160	03-36-30 03-36-40 03-36-50 03-36-60 03-36-70 03-36-80 03-36-90 03-36-100 03-36-120 03-36-140 03-36-160	03-44-30 03-44-40 03-44-50 03-44-60 03-44-70 03-44-80 03-44-90 03-44-100 03-44-120 03-44-140 03-44-160	.125 (3.2) .187 (4.8) 250 (6.35) 312 (7.9) 375 (9.5) 437 (11.1) 500 (12.7) 562 (14.3) 625 (15.9) 750 (19.1) 875 (22.2) 1.00 (25.4)
 HOLE Ø= .187±.003 (4.75 ± 0.08) PANEL THICKNESS RANGE = .090 to .125 (2.28 to 3.18)	03-43-2-30 03-43-2-40 03-43-2-50 03-43-2-60 03-43-2-70 03-43-2-80 03-43-2-90 03-43-2-100 03-43-2-120 03-43-2-140 03-43-2-160	03-39-2-30 03-39-2-40 03-39-2-50 03-39-2-60 03-39-2-70 03-39-2-80 03-39-2-90 03-39-2-100 03-39-2-120 03-39-2-140 03-39-2-160	03-35-2-30 03-35-2-40 03-35-2-50 03-35-2-60 03-35-2-70 03-35-2-80 03-35-2-90 03-35-2-100 03-35-2-120 03-35-2-140 03-35-2-160	03-36-2-30 03-36-2-40 03-36-2-50 03-36-2-60 03-36-2-70 03-36-2-80 03-36-2-90 03-36-2-100 03-36-2-120 03-36-2-140 03-36-2-160	03-44-2-30 03-44-2-40 03-44-2-50 03-44-2-60 03-44-2-70 03-44-2-80 03-44-2-90 03-44-2-100 03-44-2-120 03-44-2-140 03-44-2-160	.125 (3.2) .187 (4.8) 250 (6.35) 312 (7.9) 375 (9.5) 437 (11.1) 500 (12.7) 562 (14.3) 625 (15.9) 750 (19.1) 875 (22.2) 1.00 (25.4)
 HOLE Ø= .187±.003 (4.75 ± 0.08) PANEL THICKNESS RANGE = .031 to .078 (0.79 to 1.98)	03-43-A-30 03-43-A-40 03-43-A-50 03-43-A-60 03-43-A-70 03-43-A-80 03-43-A-90 03-43-A-100 03-43-A-120 03-43-A-140 03-43-A-160	03-39-A-30 03-39-A-40 03-39-A-50 03-39-A-60 03-39-A-70 03-39-A-80 03-39-A-90 03-39-A-100 03-39-A-120 03-39-A-140 03-39-A-160	03-35-A-30 03-35-A-40 03-35-A-50 03-35-A-60 03-35-A-70 03-35-A-80 03-35-A-90 03-35-A-100 03-35-A-120 03-35-A-140 03-35-A-160	03-36-A-30 03-36-A-40 03-36-A-50 03-36-A-60 03-36-A-70 03-36-A-80 03-36-A-90 03-36-A-100 03-36-A-120 03-36-A-140 03-36-A-160	03-44-A-30 03-44-A-40 03-44-A-50 03-44-A-60 03-44-A-70 03-44-A-80 03-44-A-90 03-44-A-100 03-44-A-120 03-44-A-140 03-44-A-160	.125 (3.2) .187 (4.8) 250 (6.35) 312 (7.9) 375 (9.5) 437 (11.1) 500 (12.7) 562 (14.3) 625 (15.9) 750 (19.1) 875 (22.2) 1.00 (25.4)
 HOLE Ø = .312±.003 ( 7.9 ± 0.08 ) PANEL THICKNESS = .250 (6.4) min.	03-43-3-20 03-43-3-30 03-43-3-40 03-43-3-50 03-43-3-60 03-43-3-70 03-43-3-80 03-43-3-90 03-43-3-100 03-43-3-120 03-43-3-140 03-43-3-160	03-39-3-20 03-39-3-30 03-39-3-40 03-39-3-50 03-39-3-60 03-39-3-70 03-39-3-80 03-39-3-90 03-39-3-100 03-39-3-120 03-39-3-140 03-39-3-160	03-35-3-20 03-35-3-30 03-35-3-40 03-35-3-50 03-35-3-60 03-35-3-70 03-35-3-80 03-35-3-90 03-35-3-100 03-35-3-120 03-35-3-140 03-35-3-160	03-36-3-20 03-36-3-30 03-36-3-40 03-36-3-50 03-36-3-60 03-36-3-70 03-36-3-80 03-36-3-90 03-36-3-100 03-36-3-120 03-36-3-140 03-36-3-160	03-44-3-20 03-44-3-30 03-44-3-40 03-44-3-50 03-44-3-60 03-44-3-70 03-44-3-80 03-44-3-90 03-44-3-100 03-44-3-120 03-44-3-140 03-44-3-160	.125 (3.2) .187 (4.8) 250 (6.35) 312 (7.9) 375 (9.5) 437 (11.1) 500 (12.7) 562 (14.3) 625 (15.9) 750 (19.1) 875 (22.2) 1.00 (25.4)

B	changed "panel thickness" to "thickness range"	03-31-11	FL	Drawn by FL	Title <b>WIRE ROUTING DEVICES</b> ALL ELECTRONICS HARDWARE INC. 2642 Corporate Parkway Algonquin, IL 60102 1 800 778 7234	Dwg. Type <b>CATALOG</b>	Issue <b>B</b>
A	Added V-0 material note	03-28-11	FL				
No	Change	Date	Init				

03-24-11

File No. twistlokcompound

03-31-11